

Mounting instructions for KLINGER Rubber-Metal-Gaskets

On principle following mounting instructions for KLINGER Rubber-Metal-Gaskets material have to taken in account:

1. Selection of the gasket

The suitable type of gasket material can be selected according the KLINGER information – first of all the chemical resistance.

2. Flanges should be parallel, metallicly clean and dry, the gasket has to be mounted centrally.

Please pay attention to the correct inner- and outer diameter, never the gaskets should tower into the throughhole!

3. The mounting of the gasket should be performed without any grease- or oil-containing separating media.

On no account oil grease containing products may be used, as they have an negative influence on the safety of the complete flange connection.

4. During installation the bolts have to be tightened in several steps, equal and crosswise.

The screws should be greased if possible.

5. “Re-tighten” is usually not necessary if a.m. references will be followed.

6. “Multi-use” of a gasket

To use a gasket more than one time can not be recommended.

If there is an demand on advice please contact a KLINGER company or an representative!

Certified acc. to DIN EN ISO 9001:2000

KLINGER GmbH
Rich.-Klinger-Strasse 8, D-65510 Idstein
Phone +49 6126 950-0
Fax +49 6126 950 340 / 950 341
e-mail: mail@klinger.de
[http:// www.klinger.de](http://www.klinger.de)

Subject to technical alterations.
Status: June 2005