

DRV 2-series



DRV 200 / 200 G

WITH FEMALE THREAD 1/4" TO 2"

Inlet pressure	max. 25 bar
Outlet pressure	0,8 – 8 bar
Seals	NBR / CR
Design	Membrane
Kvs-value	0,5 – 7,2 m³/h
Temperature range	-15 to 100°C



DRV 225 / 226

WITH FEMALE THREAD 1/4" TO 2"

Inlet pressure	max. 60 bar
Outlet pressure	1,5 – 45 bar
Seals	NBR / FPM
Design	Piston
Kvs-value	0,5 – 7,2 m³/h
Temperature range	-15 to 190°C



DRV 250

WITH FEMALE THREAD 1/4" TO 2"

Inlet pressure	max. 25 bar
Outlet pressure	0,2 – 2 bar
Seals	NBR
Design	Membrane
Kvs-value	0,5 – 7,2 m³/h
Temperature range	-15 to 100°C



DRV 230 / 230 G

WITH FLANGES DN 8 TO DN 50

Inlet pressure	max. 25 bar
Outlet pressure	0,8 – 8 bar
Seals	NBR / CR
Design	Membrane
Kvs-value	0,5 – 7,2 m³/h
Temperature range	-15 to 100°C



DRV 235

WITH FLANGES DN 8 TO DN 50

Inlet pressure	max. 40 bar
Outlet pressure	1,5 – 20 bar
Seals	NBR / FPM
Design	Piston
Kvs-value	0,5 – 7,2 m³/h
Temperature range	-15 to 190°C

DRV 3-series



DRV 302 / 303 / 308

WITH FEMALE THREAD ½" TO 2"

Inlet pressure	max. 40 bar
Outlet pressure	1,5 – 10 bar
Seals	NBR / FKM / EPDM
Design	Membrane
Kvs-value	2,9 – 13 m³/h
Temperature range	-30 to 190 °C



DRV 302 – 6 / 303 – 6

WITH FEMALE THREAD ½" TO 2"

Inlet pressure	max. 16 bar
Outlet pressure	1,5 – 6 bar
Seals	EPDM
Design	Membrane
Kvs-value	2,9 – 13 m³/h
Temperature range	-15 to 75 °C



DRV 324 / 325

WITH FEMALE THREAD ½" TO 2"

Inlet pressure	max. 40 bar
Outlet pressure	1,5 – 20 bar
Seals	NBR / FKM / EPDM
Design	Piston
Kvs-value	2,9 – 13 m³/h
Temperature range	-30 to 190 °C



DRV 350

WITH FEMALE THREAD ½" TO 2"

Inlet pressure	max. 16 bar
Outlet pressure	0,2 - 2 bar
Seals	NBR / FKM / EPDM
Design	Membrane
Kvs-value	2,9 – 13 m³/h
Temperature range	-30 to 190 °C



DRV 372 / 373 / 378

WITH FEMALE THREAD ½" TO 2"

Inlet pressure	max. 40 bar
Outlet pressure	0,5 – 9 bar
Seals	NBR / FKM / EPDM
Design	Membrane
Kvs-value	2,9 – 13 m³/h
Temperature range	-30 to 190 °C

DRV 4-series



DRV 402 / 403 / 408

WITH MALE THREAD ½" TO 2 ½"

Inlet pressure	max. 40 bar
Outlet pressure	1,5 – 10 bar
Seals	NBR / FKM / EPDM
Design	Membrane
Kvs-value	2,9 – 13 m³/h
Temperature range	-30 to 190°C



DRV 402 – 6 / 403 – 6

WITH MALE THREAD ½" TO 2 ½"

Inlet pressure	max. 16 bar
Outlet pressure	1,5 – 6 bar
Seals	EPDM
Design	Membrane
Kvs-value	2,9 – 13 m³/h
Temperature range	-15 to 75°C



DRV 424 / 425

WITH MALE THREAD ½" TO 2 ½"

Inlet pressure	max. 40 bar
Outlet pressure	1,5 – 20 bar
Seals	NBR / FKM / EPDM
Design	Piston
Kvs-value	2,9 – 13 m³/h
Temperature range	-30 to 190°C



DRV 450

WITH MALE THREAD ½" TO 2 ½"

Inlet pressure	max. 16 bar
Outlet pressure	0,2 - 2 bar
Seals	NBR / FKM / EPDM
Design	Membrane
Kvs-value	2,9 – 13 m³/h
Temperature range	-30 to 190°C



DRV 472 / 473 / 478

WITH MALE THREAD ½" TO 2 ½"

Inlet pressure	max. 40 bar
Outlet pressure	0,5 – 9 bar
Seals	NBR / FKM / EPDM
Design	Membrane
Kvs-value	2,9 – 13 m³/h
Temperature range	-30 to 190°C

DRV 5-series



DRV 502 / 508

WITH FLANGE DN 15 TO DN 80

Inlet pressure	max. 25 bar
Outlet pressure	1,5 – 10 bar
Seals	NBR / FKM / EPDM
Design	Membrane
Kvs-value	2,9 – 18 m³/h
Temperature range	-30 to 190°C



DRV 502 - 6

WITH FLANGE DN 15 TO DN 80

Inlet pressure	max. 16 bar
Outlet pressure	1,5 – 6 bar
Seals	NBR / FKM / EPDM
Design	Membrane
Kvs-value	2,9 – 18 m³/h
Temperature range	-15 to 100°C



DRV 524 / 525

WITH FLANGE DN 15 TO DN 80

Inlet pressure	max. 25 bar
Outlet pressure	1,5 – 20 bar
Seals	NBR / FKM / EPDM
Design	Piston
Kvs-value	2,9 – 18 m³/h
Temperature range	-30 to 190°C



DRV 550

WITH FLANGE DN 15 TO DN 80

Inlet pressure	max. 16 bar
Outlet pressure	0,2 – 2 bar
Seals	NBR / FKM / EPDM
Design	Membrane
Kvs-value	2,9 – 13 m³/h
Temperature range	-30 to 190°C



DRV 572 / 578

WITH FLANGE DN 15 TO DN 80

Inlet pressure	max. 25 bar
Outlet pressure	1,5 - 10 bar
Seals	NBR / FKM / EPDM
Design	Membrane
Kvs-value	2,9 – 18 m³/h
Temperature range	-30 to 190°C

DRV 6-series



DRV 602 / 608

WITH FLANGE DN 65 TO DN 150

Inlet pressure	max. 25 bar
Outlet pressure	1,5 – 10 bar
Seals	NBR / EPDM
Design	Membrane
Kvs-value	48 – 210 m³/h
Temperature range	-30 to 130°C



DRV 602 - 6

WITH FLANGE DN 65 TO DN 150

Inlet pressure	max. 16 bar
Outlet pressure	1,5 – 6 bar
Seals	EPDM
Design	Membrane
Kvs-value	48 – 210 m³/h
Temperature range	-15 to 100°C



DRV 624

WITH FLANGE DN 65 TO DN 150

Inlet pressure	max. 25 bar
Outlet pressure	4 – 12 bar
Seals	NBR
Design	Piston
Kvs-value	48 – 170 m³/h
Temperature range	-15 to 100°C



DRV 672 / 678

WITH FLANGE DN 65 TO DN 150

Inlet pressure	max. 25 bar
Outlet pressure	0,5 – 9 bar
Seals	NBR / EPDM
Design	Membrane
Kvs-value	48 – 210 m³/h
Temperature range	-30 to 130°C

DRV 6-series



DRV 602 / 608

WITH FLANGE DN 65 TO DN 150

Inlet pressure	max. 25 bar
Outlet pressure	1,5 – 10 bar
Seals	NBR / EPDM
Design	Membrane
Kvs-value	48 – 210 m³/h
Temperature range	-30 to 130°C



DRV 602 - 6

WITH FLANGE DN 65 TO DN 150

Inlet pressure	max. 16 bar
Outlet pressure	1,5 – 6 bar
Seals	EPDM
Design	Membrane
Kvs-value	48 – 210 m³/h
Temperature range	-15 to 100°C



DRV 624

WITH FLANGE DN 65 TO DN 150

Inlet pressure	max. 25 bar
Outlet pressure	4 – 12 bar
Seals	NBR
Design	Piston
Kvs-value	48 – 170 m³/h
Temperature range	-15 to 100°C



DRV 672 / 678

WITH FLANGE DN 65 TO DN 150

Inlet pressure	max. 25 bar
Outlet pressure	0,5 – 9 bar
Seals	NBR / EPDM
Design	Membrane
Kvs-value	48 – 210 m³/h
Temperature range	-30 to 130°C

DRV 7-series syrefast rustfri stål.

Varianter iht. FDA, til høje temperaturer (damp op til 200°C)



DRV 702 / 708

WITH FEMALE THREAD ½" TO 2"

Inlet pressure	max. 40 bar
Outlet pressure	1,5 – 10 bar
Seals	NBR / FKM / EPDM
Design	Membrane
Kvs-value	2,9 – 13 m³/h
Temperature range	-30 to 190 °C



DRV 703 / 773

WITH FEMALE THREAD ½" TO 1½"

Inlet pressure	max. 16 bar
Outlet pressure	1,5 – 6 bar
Seals	NBR / FKM / EPDM
Design	Membrane
Kvs-value	2,9 – 6,1 m³/h
Temperature range	-30 to 190 °C



DRV 724 / 725

WITH FEMALE THREAD ½" TO 2" *

Inlet pressure	max. 40 bar
Outlet pressure	1,5 – 20 bar
Seals	NBR / FKM / EPDM
Design	Piston
Kvs-value	2,9 – 13 m³/h
Temperature range	-30 to 190 °C



DRV 730-D

WITH FEMALE THREAD ½" TO 2"

Inlet pressure	max. 16 bar
Outlet pressure	0,3 – 2 bar
Seals	PTFE/FEPM/EPDM
Design	Piston
Kvs-value	3,0 – 12 m³/h
Temperature range	-30 to 200 °C



DRV 732-D / 738-D

WITH FEMALE THREAD ½" TO 2"

Inlet pressure	max. 16 bar
Outlet pressure	2 – 10 bar
Seals	PTFE/FEPM/EPDM
Design	Piston
Kvs-value	3,6 – 14 m³/h
Temperature range	-30 to 200 °C



DRV 750

WITH FEMALE THREAD ½" TO 2"

Inlet pressure	max. 25 bar
Outlet pressure	0,2 – 2 bar
Seals	NBR / FKM / EPDM
Design	Membrane
Kvs-value	2,9 – 13 m³/h
Temperature range	-30 to 190 °C

DRV 7-series syrefast rustfri stål.

Varianter iht. FDA, til høje temperaturer (damp op til 200°C)



DRV 702 / 708

WITH FEMALE THREAD ½" TO 2"

Inlet pressure	max. 40 bar
Outlet pressure	1,5 – 10 bar
Seals	NBR / FKM / EPDM
Design	Membrane
Kvs-value	2,9 – 13 m³/h
Temperature range	-30 to 190 °C



DRV 703 / 773

WITH FEMALE THREAD ½" TO 1½"

Inlet pressure	max. 16 bar
Outlet pressure	1,5 – 6 bar
Seals	NBR / FKM / EPDM
Design	Membrane
Kvs-value	2,9 – 6,1 m³/h
Temperature range	-30 to 190 °C



DRV 724 / 725

WITH FEMALE THREAD ½" TO 2" *

Inlet pressure	max. 40 bar
Outlet pressure	1,5 – 20 bar
Seals	NBR / FKM / EPDM
Design	Piston
Kvs-value	2,9 – 13 m³/h
Temperature range	-30 to 190 °C



DRV 730-D

WITH FEMALE THREAD ½" TO 2"

Inlet pressure	max. 16 bar
Outlet pressure	0,3 – 2 bar
Seals	PTFE/FEPM/EPDM
Design	Piston
Kvs-value	3,0 – 12 m³/h
Temperature range	-30 to 200 °C



DRV 732-D / 738-D

WITH FEMALE THREAD ½" TO 2"

Inlet pressure	max. 16 bar
Outlet pressure	2 – 10 bar
Seals	PTFE/FEPM/EPDM
Design	Piston
Kvs-value	3,6 – 14 m³/h
Temperature range	-30 to 200 °C



DRV 750

WITH FEMALE THREAD ½" TO 2"

Inlet pressure	max. 25 bar
Outlet pressure	0,2 – 2 bar
Seals	NBR / FKM / EPDM
Design	Membrane
Kvs-value	2,9 – 13 m³/h
Temperature range	-30 to 190 °C

DRV 7-series Syrefast rustfri stål.

Varianter iht. FDA, til høje temperaturer (damp op til 200°C)



DRV 772 / 778

WITH FEMALE THREAD ½" TO 2"

Inlet pressure	max. 40 bar
Outlet pressure	0,5 – 9 bar
Seals	NBR / FKM / EPDM
Design	Membrane
Kvs-value	2,9 – 13 m³/h
Temperature range	-30 to 190 °C



DRV 702-R / 708-R

WITH MALE THREAD ½" TO 2"

Inlet pressure	max. 40 bar
Outlet pressure	1,5 – 10 bar
Seals	NBR / FKM / EPDM
Design	Membrane
Kvs-value	2,9 – 13 m³/h
Temperature range	-30 to 190°C



DRV 703-R

WITH MALE THREAD ½" TO 1¼"

Inlet pressure	max. 16 bar
Outlet pressure	1,5 – 6 bar
Seals	EPDM
Design	Membrane
Kvs-value	2,9 – 6,1 m³/h
Temperature range	-30 to 75°C



DRV 724-R / 725-R

WITH MALE THREAD ½" TO 2"

Inlet pressure	max. 40 bar
Outlet pressure	1,5 – 20 bar
Seals	NBR / FKM / EPDM
Design	Piston
Kvs-value	2,9 – 13 m³/h
Temperature range	-30 to 190°C

DRV 7-series Syrefast rustfri stål.

Varianter iht. FDA, til høje temperaturer (damp op til 200°C)



DRV 730-D-R

WITH MALE THREAD ½" TO 2"

Inlet pressure	max. 16 bar
Outlet pressure	0,3 – 2 bar
Seals	PTFE/FEP/EPDM
Design	Piston
Kvs-value	3,0 – 12 m³/h
Temperature range	-30 to 200°C



DRV 732-D-R / 738-D-R

WITH MALE THREAD ½" TO 2"

Inlet pressure	max. 16 bar
Outlet pressure	2 – 10 bar
Seals	PTFE/FEP/EPDM
Design	Piston
Kvs-value	3,6 – 14 m³/h
Temperature range	-30 to 200°C



DRV 750-R

WITH MALE THREAD ½" TO 2"

Inlet pressure	max. 25 bar
Outlet pressure	0,2 – 2 bar
Seals	NBR / FKM / EPDM
Design	Membrane
Kvs-value	2,9 – 13 m³/h
Temperature range	-30 to 190°C



DRV 772-R / 778-R

WITH MALE THREAD ½" TO 2"

Inlet pressure	max. 40 bar
Outlet pressure	0,5 – 9 bar
Seals	NBR / FKM / EPDM
Design	Membrane
Kvs-value	2,9 – 13 m³/h
Temperature range	-30 to 190°C

DRV 740 / 840-series

Syrefast rustfri stål. mBar trykregulator.



740 (ISO228 / NPT)



840 (EN1092 / ANSI B16.5 150lbs)

TYPE	Maks. indgangstryk	Afgangstryk	DN	Kvs (m3/h)
DRV 743	10 bar	7-100 mbar	15-50	2,5-3
DRV 744	10 bar	30-500 mbar	15-50	2,5-3
DRV 747	10 bar	50-200 mbar	15-50	4,3-16,3
DRV 748	10 bar	150-500 mbar	15-50	4,3-16,3

Applikationer: Trykluft, neutrale gasser og neutral/aggressive væsker.

EPDM: -30°C til +120°C (FDA)

FKM: -10°C til + 180°C